

Conditions, if any, on attached page.

DEPARTMENT of ENVIRONMENT and NATURAL RESOURCES Minerals & Mining Program - Oil & Gas Section 2050 West Main, Suite #1, Rapid City, SD 57702-2493 Telephone: 605-394-2229, FAX: 605-394-5317

RECEIVED OCT 16 2006

DEPT OF ENVIRONMENT & NATURAL RESOURCES - RCRO

Well Name and Number Elevation Field and Pool, or Wildcat Proposed Depth and Formation Johnson I-9H 2919.2 GL Pete's Creek Red River B 9100' TVD; 11,312' MD; RR Size of Hole Size of Casing Weight per Foot Depth Cementing Program (amount, type, additives) Depth 1) 12-1/4" 8-5/8" 24# 2000' 635 sx Premium Lite & Class G, 3% salt + misc. surf 2) 7-7/8" 5-1/2" 15.5# & 17# 9150' 750 sx Premium Lite & Class G + various additives 3500' 3) 4) Describe Proposed Operations (Clearly State all Pertinent Details, and Give Pertinent Dates, Including Estimated Date of Starting any Proposed Work). Use Additional Page(s) if appropriate.	armene de la companya del la companya de la company	•		ONPE	וחע טו נוועות:		10011020 1101		
Name and Address of Drilling Contractor and Rig Number: Patterson Drilling Company, 1512 Larimer Street, Suite 730, Denver, CO 80202, Rig #463 (Vertical Section) C&H Well Service, Inc., PO Box 2556, Gillette, Wyoming 82717-2556, Rig #104 (Horizontal Laterals) Surface Location of Well: Qtr-Qtr, Sec, Twp, Rge, County, Feet from Nearest Lines of section, and latitude and longitude (if available): NESE Sec. 9-T22N-R6E, Harding County, 1100' FEL x 2050' FSL; Lat = 45 53' 00.32", Long = 103 22' 50.32" If Directional, top of pay and bottom hole location from nearest lines of section: West Lateral: Top est @ 8904' MD = 8850' TVD; BHL 1680' FWL x 2050' FSL, Sec. 9-T22N-R6E East Lateral: Top est @ 8913' MD = 8850' TVD; BHL 1400' FWL x 2050' FSL, Sec. 10-T22N-R6E Acres in Spacing (Drilling) Unit 480 acres Well Name and Number Elevation Field and Pool, or Wildcat Proposed Depth and Formation Johnson I-9H 2919.2 GL Pete's Creek Red River B 9100' TVD; 11,312' MD; RR Size of Hole Size of Hole Size of Casing Weight per Foot Depth Cementing Program (amount, type, additives) Depth 1) 12-14" 8-5/8" 24# 2000' 635 sx Premium Lite & Class G, 3% said + misc. surf 2) 7-7/8" 5-1/2" 15.5# & 17# 9150' 750 sx Premium Lite & Class G + various additives 3500' 30 4) Describe Proposed Operations (Clearly State all Pertinent Details, and Give Pertinent Dates, Including Estimated Date of Starting any Proposed Work). Use Additional Page(s) if appropriate. Drill vertical portion of well to 9150'. Drill 7-7/8" hole, run 5-1/2" casing. A directional survey will be run @ 100' intervals to determine the BHL of the vertical well. Move out rotary tools and move in smaller rig, mill casing windows and drill dual horizontal laterals in the Red River B". East lateral KOP approx. 8741' TVD, west lateral KOP approx. 8756' TVD. Drill 4-1/2" horizontal laterals in the Red River B". East lateral KOP approx. 8741' TVD, west lateral KOP approx. 8756' TVD. Drill 4-1/2" horizontal laterals in the PB zone. West lateral to approx. 11, 31	Type of Work: X Drill New We	ReenteryWell ONTH CAL OF	RAEY Drill Direct	ctional Well	X Oil Well				
Name and Address of Drilling Contractor and Rig Number: Patterson Drilling Company, 1512 Larimer Street, Suite 730, Denver, CO 80202, Rig #463 (Vertical Section) C&H Well Service, Inc., PO Box 2556, Gillette, Wyoning 82717-2556, Rig #104 (Horizontal Laterals) Surface Location of Well: Qu-Qir, Sec, Twp, Rge, County, Feet from Nearest Lines of section, and latitude and longitude (if available): NESE Sec. 9-T22N-R6E, Harding County, 1100' FEL x 2030' FSL; Lat = 45 53' 00.32", Long = 103 22' 50.32" If Directional, top of pay and bottom hole location from nearest lines of section: West Lateral: Top est @ 8904' MD = 8850' TVD; BHL 1680' FWL x 2050' FSL, Sec. 9-T22N-R6E East Lateral: Top est @ 8913' MD = 8850' TVD; BHL 1400' FWL x 2050' FSL, Sec. 10-T22N-R6E Acres in Spacing (Drilling) Unit 480 acres Well Name and Number Elevation Field and Pool, or Wildcat Proposed Depth and Formation	Name and Address of Operator Telephone LUFF EXPLORATION COMPANY 1580 LINCOLN STREET, SUITE 850, DENVER, CO 80203 (303) 861-2468								
Patterson Drilling Company, 1512 Larimer Street, Suite 730, Denver, CO 80202, Rig #463 (Vertical Section) C&H Well Service, Inc., PO Box 2556, Gillette, Wyoming 82717-2556, Rig #104 (Horizontal Laterals) Surface Location of Well: Qtr-Qtr, See, Twp, Rge, County, Feet from Nearest Lines of section, and latitude and longitude (if available): NESE Sec. 9-T22N-R6E, Harding County, 1100' FEL x 2050' FSL; Lat = 45 53' 00.32", Long = 103 22' 50.32" If Directional, top of pay and bottom hole location from nearest lines of section: West Lateral: Top est @ 8904' MD = 8850' TVD; BHL 1680' FWL x 2050' FSL, Sec. 9-T22N-R6E East Lateral: Top est @ 8913' MD = 8850' TVD; BHL 1400' FWL x 2050' FSL, Sec. 10-T22N-R6E Acres in Spacing (Drilling) Unit 480 acres Well Name and Number Elevation Field and Pool, or Wildcat Proposed Depth and Formation Johnson I-9H 2919.2 GL Pete's Creek Red River B 9100' TVD; 11,312' MD; RR Size of Hole Size of Casing Weight per Foot Depth Cementing Program (amount, type, additives) Depth 1) 12-1/4" 8-5/8" 24# 2000' 635 sx Premium Lite & Class G, 3% salt + misc. surf 2) 7-7/8" 5-1/2" 15.5# & 17# 9150' 750 sx Premium Lite & Class G, 3% salt + misc. surf 3) 4) Describe Proposed Operations (Clearly State all Pertinent Details, and Give Pertinent Dates, Including Estimated Date of Starting any Proposed Work). Use Additional Page(s) if appropriate. Drill vertical portion of well to 9150'. Drill 7-7/8" hole, run 5-1/2" casing. A directional survey will be run @ 100' intervals to determine the BHL of the vertical portion of well to 9150'. Drill 7-7/8" hole, run 5-1/2" casing. A directional survey will be run @ 100' intervals to determine the BHL of the vertical portion of the well and a fresh water/polymer in the horizontal sections. All drilling fluids and cuttings will be contained in a pit lined with 12 mill plastic. All liquids will be disposed of in an approved site, the liner and the cuttings will be buried in place. See attached	Merte R. & Bettyna Johnson, Box 25, Scranton, North Dakota 58651								
NESE Sec. 9-T22N-R6E, Harding County, 1100' FEL x 2050' FSL; Lat = 45 53' 00.32", Long = 103 22' 50.32" If Directional, top of pay and bottom hole location from nearest lines of section: West Lateral: Top est @ 8904' MD = 8850' TVD; BHL 1680' FWL x 2050' FSL, Sec. 9-T22N-R6E East Lateral: Top est @ 8913' MD = 8850' TVD; BHL 1400' FWL x 2050' FSL, Sec. 10-T22N-R6E Acres in Spacing (Drilling) Unit 480 acres Description of Spacing Unit 480 acres Elevation Field and Pool, or Wildcat Proposed Depth and Formation Johnson I-9H 2919.2 GL Pete's Creek Red River B 9100' TVD; 11,312' MD; RR Size of Hole Size of Casing Weight per Foot Depth Cementing Program (amount, type, additives) Depth 1) 12-14" 8-5/8" 24# 2000' 15.5# & 17# 9150' 750 sx Premium Lite & Class G, 3% salt + misc. surf 750 sx Premium Lite & Class G + various additives 3500' 30	Patterson Drilling Company, 1512 Larimer Street, Suite 730, Denver, CO 80202, Rig #463 (Vertical Section) C&H Well Service, Inc., PO Box 2556, Gillette, Wyoming 82717-2556, Rig #104 (Horizontal Laterals)								
West Lateral: Top est @ 8904' MD = 8850' TVD; BHL 1680' FWL x 2050' FSL, Sec. 9-T22N-R6E East Lateral: Top est @ 8913' MD = 8850' TVD; BHL 1400' FWL x 2050' FSL, Sec. 10-T22N-R6E Acres in Spacing (Drilling) Unit 480 acres Description of Spacing Unit 480 acres S/2 Sec. 9, & SW/4 Sec. 10-T22N-R6E Well Name and Number Elevation Field and Pool, or Wildcat Proposed Depth and Formation Johnson I-9H 2919.2 GL Pete's Creek Red River B 9100' TVD; 11,312' MD; RR Size of Hole Size of Casing Weight per Foot Depth Cementing Program (amount, type, additives) Depth 1) 12-1/4" 8-5/8" 24# 2000' 635 sx Premium Lite & Class G, 3% salt + misc. surf 2) 7-7/8" 5-1/2" 15.5# & 17# 9150' 750 sx Premium Lite & Class G + various additives 3500' 4) Describe Proposed Operations (Clearly State all Pertinent Details, and Give Pertinent Dates, Including Estimated Date of Starting any Proposed Work). Use Additional Page(s) if appropriate. Drill vertical portion of well to 9150'. Drill 7-7/8" hole, run 5-1/2" casing. A directional survey will be run @ 100' intervals to determine the BHL of the vertical well. Move out rotary tools and move in smaller rig, mill casing windows and drill dual horizontal laterals in the Red River "B". East lateral KOP approx. 8741' TVD, west lateral KOP approx. 8756' TVD. Drill 4-1/2" horizontal laterals in the "B" zone. West lateral to approx. 11, 316' MD = 8850' TVD and the east lateral to approx. 11, 302' MD = 8850' TVD. An oil base mud will be used in the vertical portion of the well and a fresh water/polymer in the horizontal sections. All drilling fluids and cuttings will be contained in a pit lined with 12 mill plastic. All liquids will be disposed of in an approved site, the liner and the cuttings will be buried in place. See attached	NESE Sec. 9-T22N-R6E, Harding County, 1100' FEL x 2050' FSL; Lat = 45 53' 00.32", Long = 103 22' 50.32"								
Well Name and Number Elevation Field and Pool, or Wildcat Proposed Depth and Formation	West Lateral: Top est @ 8904' MD = 8850' TVD; BHL 1680' FWL x 2050' FSL, Sec. 9-T22N-R6E East Lateral: Top est @ 8913' MD = 8850' TVD; BHL 1400' FWL x 2050' FSL, Sec. 10-T22N-R6E								
Johnson I-9H 2919.2 GL Pete's Creek Red River B 9100' TVD; 11,312' MD; RR Size of Hole Size of Casing Weight per Foot Depth Cementing Program (amount, type, additives) Depth 1) 12-1/4" 8-5/8" 24# 2000' 635 sx Premium Lite & Class G, 3% salt + misc. surf 2) 7-7/8" 5-1/2" 15.5# & 17# 9150' 750 sx Premium Lite & Class G + various additives 3500' 3) 4) Describe Proposed Operations (Clearly State all Pertinent Details, and Give Pertinent Dates, Including Estimated Date of Starting any Proposed Work). Use Additional Page(s) if appropriate. Drill vertical portion of well to 9150'. Drill 7-7/8" hole, run 5-1/2" casing. A directional survey will be run @ 100' intervals to determine the BHL of the vertical well. Move out rotary tools and move in smaller rig, mill casing windows and drill dual horizontal laterals in the Red River "B". East lateral KOP approx. 8741' TVD, west lateral KOP approx. 8756' TVD. Drill 4-1/2" horizontal laterals in the "B" zone. West lateral to approx. 11, 316' MD = 8850' TVD and the east lateral to approx. 11, 302' MD = 8850' TVD. An oil base mud will be used in the vertical portion of the well and a fresh water/polymer in the horizontal sections. All drilling fluids and cuttings will be contained in a pit lined with 12 mill plastic. All liquids will be disposed of in an approved site, the liner and the cuttings will be buried in place. See attached	Acres in Spacing (Drilling) Unit Description of Spacing Unit								
Size of Hole Size of Casing Weight per Foot Depth Cementing Program (amount, type, additives) Depth	Well Name and Number		Elevation	Field and Po	ol, or Wildcat	Proposed Depth and	Formation		
1) 12-1/4" 8-5/8" 24# 2000' 635 sx Premium Lite & Class G, 3% salt + misc. surf 2) 7-7/8" 5-1/2" 15.5# & 17# 9150' 750 sx Premium Lite & Class G + various additives 3500' Describe Proposed Operations (Clearly State all Pertinent Details, and Give Pertinent Dates, Including Estimated Date of Starting any Proposed Work). Use Additional Page(s) if appropriate. Drill vertical portion of well to 9150'. Drill 7-7/8" hole, run 5-1/2" casing. A directional survey will be run @ 100' intervals to determine the BHL of the vertical well. Move out rotary tools and move in smaller rig, mill casing windows and drill dual horizontal laterals in the Red River "B". East lateral KOP approx. 8741' TVD, west lateral KOP approx. 8756' TVD. Drill 4-1/2" horizontal laterals in the "B" zone. West lateral to approx. 11, 316' MD = 8850' TVD and the east lateral to approx. 11, 302' MD = 8850' TVD. An oil base mud will be used in the vertical portion of the well and a fresh water/polymer in the horizontal sections. All drilling fluids and cuttings will be contained in a pit lined with 12 mill plastic. All liquids will be disposed of in an approved site, the liner and the cuttings will be buried in place. See attached			1						
2) 7-7/8" 5-1/2" 15.5# & 17# 9150' 750 sx Premium Lite & Class G + various additives 3500' 3) 4) Describe Proposed Operations (Clearly State all Pertinent Details, and Give Pertinent Dates, Including Estimated Date of Starting any Proposed Work). Use Additional Page(s) if appropriate. Drill vertical portion of well to 9150'. Drill 7-7/8" hole, run 5-1/2" casing. A directional survey will be run @ 100' intervals to determine the BHL of the vertical well. Move out rotary tools and move in smaller rig, mill casing windows and drill dual horizontal laterals in the Red River "B". East lateral KOP approx. 8741' TVD, west lateral KOP approx. 8756' TVD. Drill 4-1/2" horizontal laterals in the "B" zone. West lateral to approx. 11, 316' MD = 8850' TVD and the east lateral to approx. 11, 302' MD = 8850' TVD. An oil base mud will be used in the vertical portion of the well and a fresh water/polymer in the horizontal sections. All drilling fluids and cuttings will be contained in a pit lined with 12 mill plastic. All liquids will be disposed of in an approved site, the liner and the cuttings will be buried in place. See attached									
Use Additional Page(s) if appropriate. Drill vertical portion of well to 9150'. Drill 7-7/8" hole, run 5-1/2" casing. A directional survey will be run @ 100' intervals to determine the BHL of the vertical well. Move out rotary tools and move in smaller rig, mill casing windows and drill dual horizontal laterals in the Red River "B". East lateral KOP approx. 8741' TVD, west lateral KOP approx. 8756' TVD. Drill 4-1/2" horizontal laterals in the "B" zone. West lateral to approx. 11, 316' MD = 8850' TVD and the east lateral to approx. 11, 302' MD = 8850' TVD. An oil base mud will be used in the vertical portion of the well and a fresh water/polymer in the horizontal sections. All drilling fluids and cuttings will be contained in a pit lined with 12 mill plastic. All liquids will be disposed of in an approved site, the liner and the cuttings will be buried in place. See attached	2) 7-7/8" 3) 4)		1			· · · · · · · · · · · · · · · · · · ·			
BHL of the vertical well. Move out rotary tools and move in smaller rig, mill casing windows and drill dual horizontal laterals in the Red River "B". East lateral KOP approx. 8741' TVD, west lateral KOP approx. 8756' TVD. Drill 4-1/2" horizontal laterals in the "B" zone. West lateral to approx. 11, 316' MD = 8850' TVD and the east lateral to approx. 11, 302' MD = 8850' TVD. An oil base mud will be used in the vertical portion of the well and a fresh water/polymer in the horizontal sections. All drilling fluids and cuttings will be contained in a pit lined with 12 mill plastic. All liquids will be disposed of in an approved site, the liner and the cuttings will be buried in place. See attached	Describe Proposed Operations (Clearly State all Pertinent Details, and Give Pertinent Dates, Including Estimated Date of Starting any Proposed Work). Use Additional Page(s) if appropriate.								
lateral to approx. 11, 316' MD = 8850' TVD and the east lateral to approx. 11, 302' MD = 8850' TVD. An oil base mud will be used in the vertical portion of the well and a fresh water/polymer in the horizontal sections. All drilling fluids and cuttings will be contained in a pit lined with 12 mill plastic. All liquids will be disposed of in an approved site, the liner and the cuttings will be buried in place. See attached									
vertical portion of the well and a fresh water/polymer in the horizontal sections. All drilling fluids and cuttings will be contained in a pit lined with 12 mill plastic. All liquids will be disposed of in an approved site, the liner and the cuttings will be buried in place. See attached									
with 12 mill plastic. All liquids will be disposed of in an approved site, the liner and the cuttings will be buried in place. See attached									
Preliminary Drilling Prognosis for additional details. Completion will be open hole in the horizontal sections. The estimated start date for	with 12 mill plastic. All liquids will be disposed of in an approved site, the liner and the cuttings will be buried in place. See attached								
location construction is Nov. 1, 2006. Estimated start date for drilling is February 1, 2006.									
Blanket South Dakota bond #4127010									
I hereby certify that the foregoing as to any work or operation performed is a true and correct report of such work or operation.									
David A. Norby Operations Manager 10/13/2006 Signature Name (Print) Title Date	Signature							··········	
FOR OFFICE USE ONLY									
Approved by: Fred wittee Title: Oil and Gas Supervisor									
Permit No. 1818 API No. 40 063 20615 Date Issued: <u>February 20, 2007</u>									